

# Agilon VX Series UPS

Single-phase, 600-1500 VA, 230 Vac

## Reliable power protection for small business and home office applications

The Agilon VX series line-interactive UPS designed with microprocessor control offers reliable and cost-effective power protection for PCs, monitors, POS, and other sensitive electronics used in home offices and small businesses. The integrated Automatic Voltage Regulation (AVR) ensures all electronics are receiving stable power while providing higher availability. The Agilon VX series' LCD display, auto-shutdown software and other superior features make these units perfect for your data protection.



### Reliability

---

- The integrated AVR (Automatic Voltage Regulation) stabilizes the output voltage for better power quality
- Excellent microprocessor control enables accurate detection of power frequency for higher reliability
- Wide input voltage range allows the UPS to work in harsh electrical environments and reduces battery discharging time
- Batteries automatically recharge even when the UPS is in off mode and the UPS can start without mains (Cold-Start)
- UPS restarts automatically while utility power is recovering
- Surge protection defends your critical load against damage

### Convenience

---

- Several standard IEC 320 output sockets simplify the connectivity to computer and IT peripherals
- Compact size saves more space for critical equipment

### Manageability

---

- Standard USB communication port enhances monitoring and manageability
- Touch screen LCD for a clear display of UPS information (Only applicable for LCD models)
- Advanced UPS management software provides remote shutdown and control



SME



Retail



## Technical Specifications

Model	VX-600VA	VX-1000VA	VX-1500VA
Topology	Line interactive		
Power Rating	600 VA 360 kW	1000 kVA 600 kW	1500 kVA 900 kW
<b>INPUT</b>			
Nominal Voltage	230 Vac, 1P2W+PE		
Voltage Range	170-280 Vac (100% load)		
Frequency Range	45-65 Hz		
Plug Type <sup>(1)</sup>	IEC		
<b>OUTPUT</b>			
Nominal Voltage	230 Vac, 1P2W+PE		
Voltage Regulation	±10%		
Frequency	50/60 ± 1 Hz		
Power Factor	0.6		
Connection <sup>(2)</sup>	IEC C13 x4		
Overload Capability	110 ± 10%: < 5 mins		
<b>EFFICIENCY</b>			
Online Mode	Up to 95%		
<b>BATTERY</b>			
Battery Type	VRLA		
Nominal Voltage	12 Vdc	24 Vdc	
Quantity	1 pcs	2 pcs	
Runtime <sup>(3)</sup>	5.7 mins	5 mins	5.5 mins
Recharge Time	6-8 hours to 90%		
<b>COMMUNICATION INTERFACE</b>			
Display	LED indicator	LCD touch panel	
Port	USB		
Audible Alarm	Battery mode, Low battery, Overload, Fault		
<b>PHYSICAL</b>			
Dimensions (W x D x H)	101 x 279 x 142 mm	130 x 320 x 182 mm	
Net Weight	4.2 kg	8.2 kg	9.7 kg
Packing Dimensions (W x D x H)	140 x 344 x 220 mm	192 x 390 x 275 mm	
Packing Weight	4.5 kg	8.9 kg	10.4 kg
<b>ENVIRONMENT</b>			
Operating Temperature	0 to 40°C		
Humidity	0-95% (non-condensing)		
Audible Noise	< 40 dBA	< 45 dBA	
Altitude	0-1000 m		
Storage Temperature	-20 to 50°C		
<b>CONFORMANCE</b>			
Safety	CE, UKCA, EAC, TISI, RCM, BIS, KC		
Sustainability	RoHS, REACH		

(1) Models with Australian, Korean, Indian, and Schuko input plugs are also available

(2) Options include Schuko, AU and IN output connections

(3) Runtime with 50% load

All specifications are subject to change without prior notice.



Delta Group



Delta Power Solutions



Delta ICT LinkedIn



Delta ICT YouTube

